

CERAMIC COATINGS WARRANTY

The warranty is for use on OEM paint by Matrix accredited professional users only.

To validate a warranty, the Matrix ceramic coating must be registered within 30 days of application by an accredited user.

Warranties can be registered via the QR code on the Matrix Ceramic packaging.

The warranty covers vehicles paintwork for:

- Loss of gloss
- Colour fading
- Total loss of water repellence

Warranty period of coverage:

MATRIX BLACK 8 year warranty

MATRIX BLUE
3 year warranty

The warranty does not cover:

- Damage to the vehicle or degradation of the coating caused by using non-specified products as detailed in the warranty.
- Any surfaces other than OEM paintwork.
- Damage to the vehicle or degradation of the coating caused by a non-recommended washing technique, including;
 automatic car washes, brushes, sponges or contaminated wash tools.
- Damage caused by stone chips, fire, collision, and extreme weather.
- · Damage caused by bird lime.
- Scratches, swirls, marring, and scrapes to the paintwork.
- Damage caused by vehicle modifications, e.g. application of decals.
- · Accidental or malicious damage.
- Damage caused by faults from the vehicle manufacturer's process and products.
- General wear and tear of the vehicle.

The warranty is void if the following conditions are not fulfilled:

- Matrix ceramic coating has been applied as detailed in the user instructions or video.
- Matrix ceramic coatings aftercare guide followed.
- Products used for aftercare of Matrix ceramic coatings as directed in the specification of the warranty.
- Annual inspection carried out within 30 days of the application anniversary and logged to continue validation of the warranty.

Limit of Liability (claims):

- Claims to Autosmart can only be made by an accredited user of Matrix ceramic coatings and not the vehicle owner.
- All Claims are at the discretion of Autosmart.

Matrix ceramic coatings aftercare product specification:

Product type	Specification	Product recommendation
Shampoo or Snowfoam	In use pH of between 6 and 8	Duofoam+ or Snowfoam Pro
	No wax content	
Quick Detailer	In use pH of between 6 and 8	Quick Detailer+ or Cobalt+
	No abrasive content	
Recharge	SiO ₂ Spray and rinse coating	Matrix Reload or Aquaseal Pro
Water Spot Remover	Must not contain a strong acid, e.g. HCl	Water Spot Remover
	Suitable mild acids include Acetic acid and Glycolic acid	
Fallout Remover	Sodium Mercaptoacetate base, colour changing product.	Red 7
Tar Remover	Alcohol or Aliphatic hydrocarbon base. Aromatic content <5%	Panel Prep+, Plus 10 or BCE